




无感箔式聚丙烯膜电容器 Polypropylene film/foil capacitor (Non-inductive)

■ 外形图 Outline Drawing

Forming Lead Shapes					
		I	II	III	IV
					
		P > F		P < F	
		0mm < P-F < 3mm	3mm < P-F < 8mm	3mm < F-P < 5mm	0mm < F-P < 3mm
		F ± 0.8mm; A < 5.0mm; B=4.5 ± 0.5mm			

■ 特点

- 膜箔式电容器，无感卷绕结构，浸渍型
- 优异的频率和温度特性
- 即使在高频下，损耗也极小
- 阻燃环氧粉末封装（UL94/V-0）

■ 主要用途

- 广泛用于高频、直流和脉冲电路中

■ 技术要求 Specifications

引用标准 Reference Standard	GB 10188 (IEC 60384-13)
气候类别 Climatic Category	40/105/21
额定温度 Rated Temperature	85℃
工作温度 Operating Temperature Range	-40℃ ~ 105℃ (+85℃ to +105℃: decreasing factor 1.25% per °C for U _R)
额定电压 Rated Voltage	100V、160V、200V、250V、400V、630V、800V
电容量范围 Capacitance Range	0.0010μF ~ 0.10μF
电容量偏差 Capacitance Tolerance	± 2%(G), ± 5%(J), ± 10%(K)
耐电压 Voltage Proof	2.0U _R (5s)
损耗角正切 Dissipation Factor	≤ 10 × 10 ⁻⁴ (1kHz, 20℃)
绝缘电阻 Insulation Resistance	≥ 50 000MΩ, C _N ≤ 0.1μF ≥ 5 000s, C _N > 0.1μF (20℃ ,100V, 1min)

■ Features

- Film/foil, non-inductive wound type, dipped
- Excellent frequency and temperature characteristics
- Very small loss even at high frequency
- Flame retardant epoxy resin powder coating (UL94/V-0)

■ Typical Application

- Widely used in high frequency, DC and pulse circuits

■ 外形尺寸 Dimensions (mm)

100Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	9.0	8.5	4.5	6.5	0.6
0.0012	9.0	9.0	5.0	6.5	0.6
0.0015	9.0	9.5	5.5	6.5	0.6
0.0016	9.0	9.5	5.5	6.5	0.6
0.0018	9.0	9.5	5.5	6.5	0.6
0.0020	9.0	8.5	4.5	6.5	0.6
0.0022	9.0	8.5	4.5	6.5	0.6
0.0024	9.0	8.5	5.0	6.5	0.6
0.0027	9.0	9.0	5.0	6.5	0.6
0.0030	9.0	9.0	5.0	6.5	0.6
0.0033	9.0	9.0	5.5	6.5	0.6
0.0036	9.0	9.5	5.5	6.5	0.6
0.0039	9.0	9.5	5.5	6.5	0.6
0.0043	9.0	9.0	5.0	6.5	0.6
0.0047	9.0	9.0	5.0	6.5	0.6
0.0051	9.0	9.5	5.5	6.5	0.6
0.0056	9.0	9.5	5.5	6.5	0.6
0.0062	9.0	9.5	6.0	6.5	0.6
0.0068	9.0	10.0	6.0	6.5	0.6
0.0075	10.0	9.5	6.0	7.5	0.6
0.0082	10.0	10.0	6.0	7.5	0.6
0.0091	10.0	10.0	6.0	7.5	0.6
0.0100	10.0	10.5	6.5	7.5	0.6
0.0120	10.0	11.0	7.0	7.5	0.6
0.0150	12.0	10.5	6.5	8.5	0.6
0.0160	12.0	10.5	6.5	8.5	0.6
0.0180	12.0	10.5	7.0	8.5	0.6
0.0200	12.0	11.0	7.0	8.5	0.6
0.0220	12.0	11.0	7.5	8.5	0.6
0.0240	12.0	11.5	7.5	8.5	0.6
0.0270	12.0	12.0	8.0	8.5	0.6
0.0300	13.5	11.5	6.5	10.0	0.6
0.0330	13.5	11.5	7.0	10.0	0.6
0.0360	13.5	12.0	7.0	10.0	0.6
0.0390	13.5	12.0	7.5	10.0	0.6
0.0430	13.5	12.5	7.5	10.0	0.6
0.0470	13.5	12.5	8.0	10.0	0.6
0.0510	13.5	13.0	8.0	10.0	0.6
0.0560	13.5	13.0	8.5	10.0	0.6
0.0620	17.0	12.5	7.5	13.0	0.6
0.0680	17.0	13.0	7.5	13.0	0.6
0.0750	17.0	13.0	8.0	13.0	0.6
0.0820	17.0	13.5	8.0	13.0	0.6
0.0910	17.0	14.0	8.5	13.0	0.6
0.1000	17.0	14.0	8.5	13.0	0.6

160Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	10.0	9.0	5.0	6.5	0.6
0.0012	10.0	9.5	5.5	6.5	0.6
0.0015	10.0	9.5	5.5	6.5	0.6
0.0016	10.0	9.5	5.5	6.5	0.6
0.0018	10.0	10.0	6.0	6.5	0.6
0.0020	10.0	9.0	5.5	6.5	0.6
0.0022	10.0	9.5	5.5	6.5	0.6
0.0024	10.0	9.5	5.5	6.5	0.6
0.0027	10.0	9.5	5.5	6.5	0.6
0.0030	10.0	10.0	6.0	6.5	0.6
0.0033	10.0	10.0	6.0	6.5	0.6
0.0036	10.0	10.0	6.0	6.5	0.6
0.0039	10.0	10.0	6.5	6.5	0.6
0.0043	10.0	10.5	6.5	6.5	0.6
0.0047	10.0	10.5	6.5	6.5	0.6
0.0051	12.0	10.0	5.5	8.5	0.6
0.0056	12.0	10.5	5.5	8.5	0.6
0.0062	12.0	10.5	6.0	8.5	0.6
0.0068	12.0	10.5	6.0	8.5	0.6
0.0075	12.0	11.0	6.0	8.5	0.6
0.0082	12.0	11.0	6.5	8.5	0.6
0.0091	12.0	11.0	6.5	8.5	0.6
0.0100	12.0	11.5	6.5	8.5	0.6
0.0120	12.0	12.0	7.0	8.5	0.6
0.0150	12.0	12.5	7.5	8.5	0.6
0.0160	12.0	12.5	8.0	8.5	0.6
0.0180	12.0	13.0	8.0	8.5	0.6
0.0200	15.0	12.0	7.0	11.0	0.6
0.0220	15.0	12.5	7.0	11.0	0.6
0.0240	15.0	12.5	7.0	11.0	0.6
0.0270	15.0	12.5	7.5	11.0	0.6
0.0300	17.0	12.0	7.0	13.0	0.6
0.0330	17.0	12.5	7.5	13.0	0.6
0.0360	17.0	12.5	7.5	13.0	0.6
0.0390	17.0	13.0	7.5	13.0	0.6
0.0430	17.0	13.0	8.0	13.0	0.6
0.0470	17.0	13.5	8.5	13.0	0.6
0.0510	17.0	14.0	8.5	13.0	0.6
0.0560	17.0	14.0	9.0	13.0	0.6
0.0620	17.0	14.5	9.0	13.0	0.6
0.0680	17.0	15.0	9.5	13.0	0.6
0.0750	22.5	13.5	8.0	19.0	0.8
0.0820	22.5	13.5	8.5	19.0	0.8
0.0910	22.5	14.0	9.0	19.0	0.8
0.1000	22.5	14.5	9.0	19.0	0.8

200Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	14.5	10.0	6.0	11.0	0.6
0.0012	14.5	10.5	6.5	11.0	0.6
0.0015	14.5	10.5	6.5	11.0	0.6
0.0016	14.5	10.5	6.0	11.0	0.6
0.0018	14.5	11.0	6.0	11.0	0.6
0.0020	14.5	11.0	6.5	11.0	0.6
0.0022	14.5	11.0	6.5	11.0	0.6
0.0024	14.5	11.5	6.5	11.0	0.6
0.0027	14.5	11.5	7.0	11.0	0.6
0.0030	14.5	11.5	7.0	11.0	0.6
0.0033	14.5	12.0	7.0	11.0	0.6
0.0036	14.5	12.0	7.5	11.0	0.6
0.0039	14.5	12.5	7.5	11.0	0.6
0.0043	14.5	12.5	8.0	11.0	0.6
0.0047	14.5	13.0	8.0	11.0	0.6
0.0051	18.0	11.5	6.5	14.0	0.6
0.0056	18.0	12.0	6.5	14.0	0.6
0.0062	18.0	12.0	7.0	14.0	0.6
0.0068	18.0	12.5	7.0	14.0	0.6
0.0075	18.0	12.5	7.5	14.0	0.6
0.0082	18.0	13.0	7.5	14.0	0.6
0.0091	18.0	14.0	7.5	14.0	0.6
0.0100	18.0	14.5	7.5	14.0	0.6
0.0120	18.0	15.0	8.0	14.0	0.6
0.0150	18.0	11.0	6.0	14.0	0.6
0.0160	18.0	11.0	6.0	14.0	0.6
0.0180	18.0	11.5	6.0	14.0	0.6
0.0200	18.0	11.5	6.5	14.0	0.6
0.0220	18.0	11.5	6.5	14.0	0.6
0.0240	18.0	12.0	6.5	14.0	0.6
0.0270	18.0	13.5	6.5	14.0	0.6
0.0300	18.0	13.5	6.5	14.0	0.6
0.0330	18.0	13.5	7.0	14.0	0.6
0.0360	18.0	14.0	7.0	14.0	0.6
0.0390	18.0	14.5	7.5	14.0	0.6
0.0430	18.0	14.5	7.5	14.0	0.6
0.0470	18.0	14.58	8.0	14.0	0.6
0.0510	22.5	14.0	7.0	19.0	0.8
0.0560	22.5	14.0	7.5	19.0	0.8
0.0620	22.5	15.5	7.5	19.0	0.8
0.0680	22.5	16.0	7.5	19.0	0.8
0.0750	22.5	16.0	8.0	19.0	0.8
0.0820	22.5	16.5	8.0	19.0	0.8
0.0910	22.5	17.0	8.5	19.0	0.8
0.1000	22.5	17.0	9.0	19.0	0.8

250Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	12.0	9.5	5.5	8.5	0.6
0.0012	12.0	10.0	6.0	8.5	0.6
0.0015	12.0	10.0	6.5	8.5	0.6
0.0016	12.0	10.5	6.5	8.5	0.6
0.0018	12.0	10.5	6.5	8.5	0.6
0.0020	12.0	9.5	5.5	8.5	0.6
0.0022	12.0	9.5	5.5	8.5	0.6
0.0024	12.0	9.5	5.5	8.5	0.6
0.0027	12.0	10.0	6.0	8.5	0.6
0.0030	12.0	10.0	6.0	8.5	0.6
0.0033	12.0	10.0	6.0	8.5	0.6
0.0036	12.0	10.5	6.5	8.5	0.6
0.0039	12.0	10.5	6.5	8.5	0.6
0.0043	12.0	10.0	6.0	8.5	0.6
0.0047	12.0	10.0	6.0	8.5	0.6

250Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0051	12.0	10.5	6.5	8.5	0.6
0.0056	12.0	10.5	6.5	8.5	0.6
0.0062	12.0	10.5	7.0	8.5	0.6
0.0068	12.0	11.0	7.0	8.5	0.6
0.0075	13.5	10.5	6.5	10.0	0.6
0.0082	13.5	10.5	6.5	10.0	0.6
0.0091	13.5	10.5	6.5	10.0	0.6
0.0100	13.5	11.0	7.0	10.0	0.6
0.0120	18.0	11.0	6.0	14.0	0.6
0.0150	18.0	11.5	6.0	14.0	0.6
0.0160	18.0	11.5	6.5	14.0	0.6
0.0180	18.0	11.5	6.5	14.0	0.6
0.0200	18.0	12.0	6.5	14.0	0.6
0.0220	18.0	12.0	7.0	14.0	0.6
0.0240	18.0	13.5	6.5	14.0	0.6

250Vdc					
C _N (μF)	W max	H max	T max	P	d
0.027	18.0	13.5	7.0	14.0	0.6
0.030	18.0	14.0	7.0	14.0	0.6
0.033	18.0	14.0	7.5	14.0	0.6
0.036	18.0	14.5	7.5	14.0	0.6
0.039	18.0	14.5	8.0	14.0	0.6
0.043	18.0	15.0	8.0	14.0	0.6
0.047	18.0	15.5	8.5	14.0	0.6
0.051	22.5	15.5	7.5	19.0	0.8
0.056	22.5	16.0	8.0	19.0	0.8
0.062	22.5	16.0	8.5	19.0	0.8
0.068	22.5	16.5	8.5	19.0	0.8
0.075	22.5	17.0	9.0	19.0	0.8
0.082	22.5	17.0	9.5	19.0	0.8
0.091	22.5	17.5	9.5	19.0	0.8
0.100	22.5	18.0	10.0	19.0	0.8

备注: “-”表示容量偏差。 “-”=capacitance tolerance code, K=±10%,J=±5%,G=±2%

■ 外形尺寸 Dimensions (mm)

400Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	13.5	10.0	6.0	10.0	0.6
0.0012	13.5	10.5	6.5	10.0	0.6
0.0015	13.5	10.5	6.5	10.0	0.6
0.0016	13.5	10.0	6.0	10.0	0.6
0.0018	13.5	10.0	6.5	10.0	0.6
0.0020	13.5	9.0	5.5	10.0	0.6
0.0022	13.5	9.5	5.5	10.0	0.6
0.0024	13.5	9.5	5.5	10.0	0.6
0.0027	13.5	9.5	5.5	10.0	0.6
0.0030	13.5	9.5	6.0	10.0	0.6
0.0033	13.5	10.0	6.0	10.0	0.6
0.0036	15.0	11.0	5.5	11.0	0.6
0.0039	15.0	11.0	6.0	11.0	0.6
0.0043	15.0	11.0	6.0	11.0	0.6
0.0047	15.0	11.5	6.0	11.0	0.6
0.0051	15.0	11.5	6.5	11.0	0.6
0.0056	15.0	11.5	6.5	11.0	0.6
0.0062	15.0	12.0	6.5	11.0	0.6
0.0068	15.0	12.0	7.0	11.0	0.6
0.0075	15.0	12.0	7.0	11.0	0.6
0.0082	15.0	12.5	7.0	11.0	0.6
0.0091	15.0	12.5	7.5	11.0	0.6
0.0100	15.0	13.0	8.0	11.0	0.6

630Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	14.5	10.0	6.0	11.0	0.6
0.0012	14.5	10.5	6.5	11.0	0.6
0.0015	14.5	10.5	6.5	11.0	0.6
0.0016	14.5	10.5	6.0	11.0	0.6
0.0018	14.5	11.0	6.0	11.0	0.6
0.0020	14.5	11.0	6.5	11.0	0.6
0.0022	14.5	11.0	6.5	11.0	0.6
0.0024	14.5	11.5	6.5	11.0	0.6
0.0027	14.5	11.5	7.0	11.0	0.6
0.0030	14.5	11.5	7.0	11.0	0.6
0.0033	14.5	12.0	7.0	11.0	0.6
0.0036	14.5	12.0	7.5	11.0	0.6
0.0039	14.5	12.5	7.5	11.0	0.6
0.0043	14.5	12.5	8.0	11.0	0.6
0.0047	14.5	13.0	8.0	11.0	0.6
0.0051	18.0	11.5	6.5	14.0	0.6
0.0056	18.0	12.0	6.5	14.0	0.6
0.0062	18.0	12.0	7.0	14.0	0.6
0.0068	18.0	12.5	7.0	14.0	0.6
0.0075	18.0	12.5	7.5	14.0	0.6
0.0082	18.0	13.0	7.5	14.0	0.6
0.0091	18.0	14.0	7.5	14.0	0.6
0.0100	18.0	14.5	7.5	14.0	0.6

800Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	14.5	10.0	6.0	11.0	0.6
0.0012	14.5	10.0	6.0	11.0	0.6
0.0015	14.5	10.5	6.5	11.0	0.6
0.0016	14.5	10.5	6.5	11.0	0.6
0.0018	14.5	11.0	7.0	11.0	0.6
0.0020	16.0	11.0	6.5	12.5	0.6
0.0022	16.0	11.5	6.5	12.5	0.6
0.0024	16.0	11.5	6.5	12.5	0.6
0.0027	16.0	11.5	7.0	12.5	0.6
0.0030	16.0	12.0	7.0	12.5	0.6
0.0033	16.0	12.0	7.5	12.5	0.6
0.0036	16.0	12.5	7.5	12.5	0.6
0.0039	16.0	12.5	8.0	12.5	0.6
0.0043	18.0	12.5	7.5	14.0	0.6
0.0047	18.0	13.0	7.5	14.0	0.6
0.0051	18.0	13.0	8.0	14.0	0.6
0.0056	18.0	13.5	8.0	15.0	0.8
0.0062	18.0	14.5	8.0	15.0	0.8
0.0068	18.0	15.0	8.0	15.0	0.8
0.0075	18.0	15.5	8.5	15.0	0.8
0.0082	18.0	15.5	8.5	15.0	0.8
0.0091	22.5	14.5	8.0	19.0	0.8
0.0100	22.5	15.0	8.0	19.0	0.8

备注：“-”表示容量偏差。 “-”=capacitance tolerance code, K=±10%,J=±5%,G=±2%

■ 外形尺寸 Dimensions (mm)

100Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	9.0	8.5	4.5	6.5	0.6
0.0012	9.0	9.0	5.0	6.5	0.6
0.0015	9.0	9.5	5.5	6.5	0.6
0.0016	9.0	9.5	5.5	6.5	0.6
0.0018	9.0	9.5	5.5	6.5	0.6
0.0020	9.0	8.5	4.5	6.5	0.6
0.0022	9.0	8.5	4.5	6.5	0.6
0.0024	9.0	8.5	5.0	6.5	0.6
0.0027	9.0	9.0	5.0	6.5	0.6
0.0030	9.0	9.0	5.0	6.5	0.6
0.0033	9.0	9.0	5.5	6.5	0.6
0.0036	9.0	9.5	5.5	6.5	0.6
0.0039	9.0	9.5	5.5	6.5	0.6
0.0043	9.0	9.0	5.0	6.5	0.6
0.0047	9.0	9.0	5.0	6.5	0.6
0.0051	9.0	9.5	5.5	6.5	0.6
0.0056	9.0	9.5	5.5	6.5	0.6
0.0062	9.0	9.5	6.0	6.5	0.6
0.0068	9.0	10.0	6.0	6.5	0.6
0.0075	10.0	9.5	6.0	7.5	0.6
0.0082	10.0	10.0	6.0	7.5	0.6
0.0091	10.0	10.0	6.0	7.5	0.6
0.0100	10.0	10.5	6.5	7.5	0.6
0.0120	10.0	11.0	7.0	7.5	0.6
0.0150	12.0	10.5	6.5	8.5	0.6
0.0160	12.0	10.5	6.5	8.5	0.6
0.0180	12.0	10.5	7.0	8.5	0.6
0.0200	12.0	11.0	7.0	8.5	0.6
0.0220	12.0	11.0	7.5	8.5	0.6
0.0240	12.0	11.5	7.5	8.5	0.6
0.0270	12.0	12.0	8.0	8.5	0.6
0.0300	13.5	11.5	6.5	10.0	0.6
0.0330	13.5	11.5	7.0	10.0	0.6
0.0360	13.5	12.0	7.0	10.0	0.6
0.0390	13.5	12.0	7.5	10.0	0.6
0.0430	13.5	12.5	7.5	10.0	0.6
0.0470	13.5	12.5	8.0	10.0	0.6
0.0510	13.5	13.0	8.0	10.0	0.6
0.0560	13.5	13.0	8.5	10.0	0.6
0.0620	17.0	12.5	7.5	13.0	0.6
0.0680	17.0	13.0	7.5	13.0	0.6
0.0750	17.0	13.0	8.0	13.0	0.6
0.0820	17.0	13.5	8.0	13.0	0.6
0.0910	17.0	14.0	8.5	13.0	0.6
0.1000	17.0	14.0	8.5	13.0	0.6

160Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	10.0	9.0	5.0	6.5	0.6
0.0012	10.0	9.5	5.5	6.5	0.6
0.0015	10.0	9.5	5.5	6.5	0.6
0.0016	10.0	9.5	5.5	6.5	0.6
0.0018	10.0	10.0	6.0	6.5	0.6
0.0020	10.0	9.0	5.5	6.5	0.6
0.0022	10.0	9.5	5.5	6.5	0.6
0.0024	10.0	9.5	5.5	6.5	0.6
0.0027	10.0	9.5	5.5	6.5	0.6
0.0030	10.0	10.0	6.0	6.5	0.6
0.0033	10.0	10.0	6.0	6.5	0.6
0.0036	10.0	10.0	6.0	6.5	0.6
0.0039	10.0	10.0	6.5	6.5	0.6
0.0043	10.0	10.5	6.5	6.5	0.6
0.0047	10.0	10.5	6.5	6.5	0.6
0.0051	12.0	10.0	5.5	8.5	0.6
0.0056	12.0	10.5	5.5	8.5	0.6
0.0062	12.0	10.5	6.0	8.5	0.6
0.0068	12.0	10.5	6.0	8.5	0.6
0.0075	12.0	11.0	6.0	8.5	0.6
0.0082	12.0	11.0	6.5	8.5	0.6
0.0091	12.0	11.0	6.5	8.5	0.6
0.0100	12.0	11.5	6.5	8.5	0.6
0.0120	12.0	12.0	7.0	8.5	0.6
0.0150	12.0	12.5	7.5	8.5	0.6
0.0160	12.0	12.5	8.0	8.5	0.6
0.0180	12.0	13.0	8.0	8.5	0.6
0.0200	15.0	12.0	7.0	11.0	0.6
0.0220	15.0	12.5	7.0	11.0	0.6
0.0240	15.0	12.5	7.0	11.0	0.6
0.0270	15.0	12.5	7.5	11.0	0.6
0.0300	17.0	12.0	7.0	13.0	0.6
0.0330	17.0	12.5	7.5	13.0	0.6
0.0360	17.0	12.5	7.5	13.0	0.6
0.0390	17.0	13.0	7.5	13.0	0.6
0.0430	17.0	13.0	8.0	13.0	0.6
0.0470	17.0	13.5	8.5	13.0	0.6
0.0510	17.0	14.0	8.5	13.0	0.6
0.0560	17.0	14.0	9.0	13.0	0.6
0.0620	17.0	14.5	9.0	13.0	0.6
0.0680	17.0	15.0	9.5	13.0	0.6
0.0750	22.5	13.5	8.0	19.0	0.8
0.0820	22.5	13.5	8.5	19.0	0.8
0.0910	22.5	14.0	9.0	19.0	0.8
0.1000	22.5	14.5	9.0	19.0	0.8

200Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	14.5	10.0	6.0	11.0	0.6
0.0012	14.5	10.5	6.5	11.0	0.6
0.0015	14.5	10.5	6.5	11.0	0.6
0.0016	14.5	10.5	6.0	11.0	0.6
0.0018	14.5	11.0	6.0	11.0	0.6
0.0020	14.5	11.0	6.5	11.0	0.6
0.0022	14.5	11.0	6.5	11.0	0.6
0.0024	14.5	11.5	6.5	11.0	0.6
0.0027	14.5	11.5	7.0	11.0	0.6
0.0030	14.5	11.5	7.0	11.0	0.6
0.0033	14.5	12.0	7.0	11.0	0.6
0.0036	14.5	12.0	7.5	11.0	0.6
0.0039	14.5	12.5	7.5	11.0	0.6
0.0043	14.5	12.5	8.0	11.0	0.6
0.0047	14.5	13.0	8.0	11.0	0.6
0.0051	18.0	11.5	6.5	14.0	0.6
0.0056	18.0	12.0	6.5	14.0	0.6
0.0062	18.0	12.0	7.0	14.0	0.6
0.0068	18.0	12.5	7.0	14.0	0.6
0.0075	18.0	12.5	7.5	14.0	0.6
0.0082	18.0	13.0	7.5	14.0	0.6
0.0091	18.0	14.0	7.5	14.0	0.6
0.0100	18.0	14.5	7.5	14.0	0.6
0.0120	18.0	15.0	8.0	14.0	0.6
0.0150	18.0	11.0	6.0	14.0	0.6
0.0160	18.0	11.0	6.0	14.0	0.6
0.0180	18.0	11.5	6.0	14.0	0.6
0.0200	18.0	11.5	6.5	14.0	0.6
0.0220	18.0	11.5	6.5	14.0	0.6
0.0240	18.0	12.0	6.5	14.0	0.6
0.0270	18.0	13.5	6.5	14.0	0.6
0.0300	18.0	13.5	6.5	14.0	0.6
0.0330	18.0	13.5	7.0	14.0	0.6
0.0360	18.0	14.0	7.0	14.0	0.6
0.0390	18.0	14.5	7.5	14.0	0.6
0.0430	18.0	14.5	7.5	14.0	0.6
0.0470	18.0	14.58	8.0	14.0	0.6
0.0510	22.5	14.0	7.0	19.0	0.8
0.0560	22.5	14.0	7.5	19.0	0.8
0.0620	22.5	15.5	7.5	19.0	0.8
0.0680	22.5	16.0	7.5	19.0	0.8
0.0750	22.5	16.0	8.0	19.0	0.8
0.0820	22.5	16.5	8.0	19.0	0.8
0.0910	22.5	17.0	8.5	19.0	0.8
0.1000	22.5	17.0	9.0	19.0	0.8

250Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0010	12.0	9.5	5.5	8.5	0.6
0.0012	12.0	10.0	6.0	8.5	0.6
0.0015	12.0	10.0	6.5	8.5	0.6
0.0016	12.0	10.5	6.5	8.5	0.6
0.0018	12.0	10.5	6.5	8.5	0.6
0.0020	12.0	9.5	5.5	8.5	0.6
0.0022	12.0	9.5	5.5	8.5	0.6
0.0024	12.0	9.5	5.5	8.5	0.6
0.0027	12.0	10.0	6.0	8.5	0.6
0.0030	12.0	10.0	6.0	8.5	0.6
0.0033	12.0	10.0	6.0	8.5	0.6
0.0036	12.0	10.5	6.5	8.5	0.6
0.0039	12.0	10.5	6.5	8.5	0.6
0.0043	12.0	10.0	6.0	8.5	0.6
0.0047	12.0	10.0	6.0	8.5	0.6

250Vdc					
C _N (μF)	W max	H max	T max	P	d
0.0051	12.0	10.5	6.5	8.5	0.6
0.0056	12.0	10.5	6.5	8.5	0.6
0.0062	12.0	10.5	7.0	8.5	0.6
0.0068	12.0	11.0	7.0	8.5	0.6
0.0075	13.5	10.5	6.5	10.0	0.6
0.0082	13.5	10.5	6.5	10.0	0.6
0.0091	13.5	10.5	6.5	10.0	0.6
0.0100	13.5	11.0	7.0	10.0	0.6
0.0120	18.0	11.0	6.0	14.0	0.6
0.0150	18.0	11.5	6.0	14.0	0.6
0.0160	18.0	11.5	6.5	14.0	0.6
0.0180	18.0	11.5	6.5	14.0	0.6
0.0200	18.0	12.0	6.5	14.0	0.6
0.0220	18.0	12.0	7.0	14.0	0.6
0.0240	18.0	13.5	6.5	14.0	0.6

250Vdc					
C _N (μF)	W max	H max	T max	P	d
0.027	18.0	13.5	7.0	14.0	0.6
0.030	18.0	14.0	7.0	14.0	0.6
0.033	18.0	14.0	7.5	14.0	0.6
0.036	18.0	14.5	7.5	14.0	0.6
0.039	18.0	14.5	8.0	14.0	0.6
0.043	18.0	15.0	8.0	14.0	0.6
0.047	18.0	15.5	8.5	14.0	0.6
0.051	22.5	15.5	7.5	19.0	0.8
0.056	22.5	16.0	8.0	19.0	0.8
0.062	22.5	16.0	8.5	19.0	0.8
0.068	22.5	16.5	8.5	19.0	0.8
0.075	22.5	17.0	9.0	19.0	0.8
0.082	22.5	17.0	9.5	19.0	0.8
0.091	22.5	17.5	9.5	19.0	0.8
0.100	22.5	18.0	10.0	19.0	0.8

备注: “-”表示容量偏差。 “-” =capacitance tolerance code, K=±10%,J=±5%,G=±2%.

■ 外形尺寸 Dimensions (mm)

400Vdc					
C _N (μ F)	W max	H max	T max	P	d
0.0010	13.5	10.0	6.0	10.0	0.6
0.0012	13.5	10.5	6.5	10.0	0.6
0.0015	13.5	10.5	6.5	10.0	0.6
0.0016	13.5	10.0	6.0	10.0	0.6
0.0018	13.5	10.0	6.5	10.0	0.6
0.0020	13.5	9.0	5.5	10.0	0.6
0.0022	13.5	9.5	5.5	10.0	0.6
0.0024	13.5	9.5	5.5	10.0	0.6
0.0027	13.5	9.5	5.5	10.0	0.6
0.0030	13.5	9.5	6.0	10.0	0.6
0.0033	13.5	10.0	6.0	10.0	0.6
0.0036	15.0	11.0	5.5	11.0	0.6
0.0039	15.0	11.0	6.0	11.0	0.6
0.0043	15.0	11.0	6.0	11.0	0.6
0.0047	15.0	11.5	6.0	11.0	0.6
0.0051	15.0	11.5	6.5	11.0	0.6
0.0056	15.0	11.5	6.5	11.0	0.6
0.0062	15.0	12.0	6.5	11.0	0.6
0.0068	15.0	12.0	7.0	11.0	0.6
0.0075	15.0	12.0	7.0	11.0	0.6
0.0082	15.0	12.5	7.0	11.0	0.6
0.0091	15.0	12.5	7.5	11.0	0.6
0.0100	15.0	13.0	8.0	11.0	0.6

630Vdc					
C _N (μ F)	W max	H max	T max	P	d
0.0010	14.5	10.0	6.0	11.0	0.6
0.0012	14.5	10.5	6.5	11.0	0.6
0.0015	14.5	10.5	6.5	11.0	0.6
0.0016	14.5	10.5	6.0	11.0	0.6
0.0018	14.5	11.0	6.0	11.0	0.6
0.0020	14.5	11.0	6.5	11.0	0.6
0.0022	14.5	11.0	6.5	11.0	0.6
0.0024	14.5	11.5	6.5	11.0	0.6
0.0027	14.5	11.5	7.0	11.0	0.6
0.0030	14.5	11.5	7.0	11.0	0.6
0.0033	14.5	12.0	7.0	11.0	0.6
0.0036	14.5	12.0	7.5	11.0	0.6
0.0039	14.5	12.5	7.5	11.0	0.6
0.0043	14.5	12.5	8.0	11.0	0.6
0.0047	14.5	13.0	8.0	11.0	0.6
0.0051	18.0	11.5	6.5	14.0	0.6
0.0056	18.0	12.0	6.5	14.0	0.6
0.0062	18.0	12.0	7.0	14.0	0.6
0.0068	18.0	12.5	7.0	14.0	0.6
0.0075	18.0	12.5	7.5	14.0	0.6
0.0082	18.0	13.0	7.5	14.0	0.6
0.0091	18.0	14.0	7.5	14.0	0.6
0.0100	18.0	14.5	7.5	14.0	0.6

800Vdc					
C _N (μ F)	W max	H max	T max	P	d
0.0010	14.5	10.0	6.0	11.0	0.6
0.0012	14.5	10.0	6.0	11.0	0.6
0.0015	14.5	10.5	6.5	11.0	0.6
0.0016	14.5	10.5	6.5	11.0	0.6
0.0018	14.5	11.0	7.0	11.0	0.6
0.0020	16.0	11.0	6.5	12.5	0.6
0.0022	16.0	11.5	6.5	12.5	0.6
0.0024	16.0	11.5	6.5	12.5	0.6
0.0027	16.0	11.5	7.0	12.5	0.6
0.0030	16.0	12.0	7.0	12.5	0.6
0.0033	16.0	12.0	7.5	12.5	0.6
0.0036	16.0	12.5	7.5	12.5	0.6
0.0039	16.0	12.5	8.0	12.5	0.6
0.0043	18.0	12.5	7.5	14.0	0.6
0.0047	18.0	13.0	7.5	14.0	0.6
0.0051	18.0	13.0	8.0	14.0	0.6
0.0056	18.0	13.5	8.0	15.0	0.8
0.0062	18.0	14.5	8.0	15.0	0.8
0.0068	18.0	15.0	8.0	15.0	0.8
0.0075	18.0	15.5	8.5	15.0	0.8
0.0082	18.0	15.5	8.5	15.0	0.8
0.0091	22.5	14.5	8.0	19.0	0.8
0.0100	22.5	15.0	8.0	19.0	0.8

备注：“-”表示容量偏差。 “-”=capacitance tolerance code, K=±10%,J=±5%,G=±2%